



DISTINCTIVE TRACKS AND POLES LTD - ROMAN BLIND MEASURE SHEET



Company name:-					Order No:-	Required by date:-					
	Headrail only or complete kit	Quantity	Blind Width (Min - 38CM)	Recess sizes given? Y/N	Gear ratio (1:1 or 1:4)	Break Device required?	Chain side RH/LH	Chain colour	Requested Chain drop	Installation height	Reference
1											
2											
3											
4											
5											
6											
7											
8											
9											
10											
11											
12											
13											
Notes:- (Please include details of reduction in Bottom bar and Rods Here, if required. Unless previously communicated to us.)											

The installation height must be provided in order for the blind to comply with the below legislation. If the installation height is not provided chains will be made as below.

<u>Child Safety Legislation - EN 13120</u>	
Operating loop for chain retainer (will be supplied as standard and MUST be fitted)	
Installation height	Chain length
Known	Distance from floor to bottom of operating chain shall be at least 1.5 m
Not known drop, less than 2.5 m	Length of operating chain loop shall be equal to or less than 1m
Not known Drop, more than 2.5 m	Shall be equal to or less than drop of blind less 1.5 m
Operating loop for Child Safety Device (BREAKAWAY SYSTEM)	
Installation height	Chain length
Known	Distance from floor to bottom of pull cords shall be at least 0.6m
Unknown	Less than or equal to 2/3rd drop of the blind

--Please note-- Recess Sizes
If YES allowance will be made for fitting (usually 1cm) if NO, blind(s) will be made to exact sizes given.
Chain Colours
Brushed Chrome, Antique Brass, Black Nickel and white (white available in set sizes of 25cm increments only, enquire for information)
Gear Drives
Standard 1:1 geared drive max weight 6KG of fabric, 1:4 geared drive max weight 8KG of fabric. Fly wheel break devices:- 1:1 gear 3.5KG max fabric weight and 1:4 gear 10KG Max fabric weight.